

**Battery powered plastic strapping tools – the new generation**



**Characteristics**

Strapping qualities:		Polypropylene (PP) and Polyester (PET)
Strapping dimensions:	widths	10.0 – 16.0 mm / 3/8 – 5/8"
	thicknesses	0.40 – 1.05 mm / .016 - .041"
Weight:		4.1 kg / 9.0 lbs
Dimension:		L355 x W122 x H128 mm
Average seal strength:		up to 75% (dependent on strap quality)
Strap tension:		300 – 2400 N / 67 – 540 lbs (adjustable)
Tensioning speed:		145 – 195 mm/s / 5.7 – 7.7 inch/s
Power supply:	Battery	14.4VDC / 2.4 Ah NiCD
	Battery	14.4VDC / 3.0 Ah NiMH
Suspension bracket (optional)		

**Advantages**

- Ergonomic design with thin handle
- Well balanced and very light tool good for all strapping positions
- Simple one-handed operation
- Very high tension force with adjustable tension speed
- Tension force and sealing time adjustable
- Easy strap threading; Both straps are inserted together
- Welding lever locks in bottom position and allows the preparation of the next strapping during welding and cooling
- Tools welds without tension (strap repair)
- Quick battery exchange

**Chart of types model P324**

Item No.	Model	Strap widths		Strap thicknesses		Max. Tension		Tension speed	
		mm	inch	mm	inch	N	lbs	mm/sec.	inch/sec.
43.0601	P324/10/0.4-0.64	10.0	3/8"	0.40-0.64	.016-.025	2400	540	145-195	5.7-7.7
43.0602	P324/10/0.65-1.05	10.0	3/8"	0.65-1.05	.026-.041	2400	540	145-195	5.7-7.7
43.0611	P324/11.1/0.4-0.64	11.1	7/16"	0.40-0.64	.016-.025	2400	540	145-195	5.7-7.7
43.0612	P324/11.1/0.65-1.05	11.1	7/16"	0.65-1.05	.026-.041	2400	540	145-195	5.7-7.7
43.0621	P324/12/0.4-0.64	12		0.40-0.64	.016-.025	2400	540	145-195	5.7-7.7
43.0622	P324/12/0.65-1.05	12		0.65-1.05	.026-.041	2400	540	145-195	5.7-7.7
43.0623	P324/12.7/0.4-0.64	12.7	1/2"	0.40-0.64	.016-.025	2400	540	145-195	5.7-7.7
43.0624	P324/12.7/0.65-1.05	12.7	1/2"	0.65-1.05	.026-.041	2400	540	145-195	5.7-7.7
43.0631	P324/13/0.4-0.64	13		0.40-0.64	.016-.025	2400	540	145-195	5.7-7.7
43.0632	P324/13/0.65-1.05	13		0.65-1.05	.026-.041	2400	540	145-195	5.7-7.7
43.0651	P324/15/0.4-0.64	15		0.40-0.64	.016-.025	2400	540	145-195	5.7-7.7
43.0652	P324/15/0.65-1.05	15		0.65-1.05	.026-.041	2400	540	145-195	5.7-7.7
43.0653	P324/15.5/0.4-0.64	15.5		0.40-0.64	.016-.025	2400	540	145-195	5.7-7.7
43.0654	P324/15.5/0.65-1.05	15.5		0.65-1.05	.026-.041	2400	540	145-195	5.7-7.7
43.0661	P324/16/0.4-0.64	16	5/8"	0.40-0.64	.016-.025	2400	540	145-195	5.7-7.7
43.0662	P324/16/0.65-1.05	16	5/8"	0.65-1.05	.026-.041	2400	540	145-195	5.7-7.7

**Battery chargers for model P324**

Item No.	Model	Charging type	Tension	Countries
N5.4414	Battery standard charger	NiCd & NiMH	220-240 V / 50-60 Hz	A, B, BG, BIH, BOL, BR, CH, CL, CZ, D, DK, DZ, E, EAS, EST, ET, EY, F, FIN, GE, GR, H, HK, HR, I, IL, IND, IR, IRQ, IS, JOR, KSA, KWT, L, LAR, LT, LV, MA, MC, MK, MOC, N, NL, P, PK, PE, PL, PRC, PY, RA, RCH, RI, RL, RO, ROK, ROU, RP, RUS, S, SK, SLO, SYR, THA, TN, TR, UA, UAE, YU, YV, Z, ZA, ZW
N5.4422	Battery turbo charger	NiCd & NiMH	220-240 V / 50-60 Hz	(same as N5.4414)
N5.4416	Battery standard charger	NiCd & NiMH	220-240 V / 50-60 Hz	BRN, BRU, CY, EAK, EAT, GB, IRL, M, MAL, OM, SGP, Y
N5.4428	Battery turbo charger	NiCd & NiMH	220-240 V / 50-60 Hz	(same as N5.4416)
N5.4426	Battery turbo charger	NiCd & NiMH	110 V / 50 Hz	GB
N5.4418	Battery standard charger	NiCd & NiMH	230-240 V / 50-60 Hz	AUS, NZ
N5.4430	Battery turbo charger	NiCd & NiMH	230-240 V / 50-60 Hz	(same as N5.4418)
N5.4424	Battery turbo charger	NiCd & NiMH	120 V / 50-60 Hz	BR, C, CDN, CO, CR, DOM, EC, GCA, J, JA, KSA, LB, MEX, NIC, PA, Puerto Rico, RC, RP, USA, YV
N5.4420	Battery standard charger	NiCd & NiMH	220 V / 60 Hz	ROK
N5.4407	Battery mobile charger	NiCd only	-	all countries

**Replacement battery for model P324**

---

Item No.	Model	Tension	Power
N5.4309	Accu NiCd	14.4VDC	2.4 Ah
N5.4316	Accu NiMH	14.4VDC	3.0 Ah

**Accessories**

---

P32.0112	Standard suspension bracket
P32.0137	Suspension bracket for alternating positions
P32.0111	Wearing plate for rough surfaces
P32.2061	Turning button kit